MKANGO RESOURCES LTD. Suite 1400, 700-2nd Street S.W. Calgary, Alberta T2P 4V5

NEWS RELEASE

MKANGO FILES TECHNICAL REPORT FOR THE MAIDEN INDICATED AND INFERRED MINERAL RESOURCE ESTIMATE FOR THE SONGWE RARE EARTH PROJECT

Calgary, Alberta: November 26th, 2012 – Mkango Resources Ltd. (TSXV-MKA) (the "**Corporation**" or "**Mkango**") is pleased to announce that it has filed a Technical Report (the "Report") for the Songwe rare earth project in Malawi. The Mineral Resource estimates from the Report, as previously announced in the News Release of 10th October 2012, are summarised below and in the tables thereafter.

Cut-off grade	In-situ Indicated Mineral	In-situ Inferred Mineral
	Resource estimate	Resource estimate
1.0% TREO	13.2 mt grading 1.62% TREO	18.6 mt grading 1.38% TREO
1.5% TREO	6.2 mt grading 2.05% TREO	5.1 mt grading 1.83% TREO

TREO – total rare earth oxides. In-situ - no geological losses applied. mt - million tonnes

- NI 43-101 technical report filed, entitled NI 43-101 Technical Report and Mineral Resource Estimate for the Songwe Hill Rare Earth Element (REE) Project, Phalombe District, Republic of Malawi, and available on www.sedar.com
- The in-situ Indicated and Inferred mineral resource estimates at the chosen base case cut-off grade of 1.0% TREO represent a major milestone in the development of the project
- Substantial tonnages at a higher grade are also generated at a higher cut-off grade of 1.5% TREO
- The mineralized zones are untested at depths greater than 350 m below the surface of Songwe Hill and are open laterally to the northeast and southwest, with additional regional exploration potential
- The Indicated component comprises approximately 41.5% of the mineral resource and 45.4% of the estimated contained TREO at a 1.0% TREO cut-off grade, and, following the results of ongoing metallurgical studies, it may form the initial basis for commencement of a pre-feasibility study
- Heavy rare earths as a percentage of total rare earths are 7.1% and 7.4% for Indicated and Inferred mineral resource estimates, respectively, at a 1.0% TREO cut-off grade

Mineral Resource Estimate

The Report was independently prepared by The MSA Group of South Africa ("MSA") and Dr. Scott Swinden of Swinden Geoscience Consultants Ltd, the "Qualified Person" (QP), who together have currently identifed 1.0% TREO as an appropriate base case cut-off grade for the mineral resource estimate. This will be further investigated on completion of metallurgical test work. The *In-situ* mineral resource estimates at different cut-off grades are illustrated in Table 1.

C	.5% TREO cut	off grade		1	L.0% TREO cut	off grade		1.5% TREO cut off grade							
	Million	TREO	TREO		Million	TREO	TREO		Million	TREO	TREO				
	tonnes	%	tonnes		tonnes	%	tonnes		tonnes	%	tonnes				
Indicated				Indicated				Indicated							
Carbonatite	16.31	1.35	219,978	Carbonatite	11.10	1.62	179,499	Carbonatite	5.26	2.03	106,886				
Fenite	2.71	1.18	31,912	Fenite	1.37	1.61	22,145	Fenite	0.59	2.11	12,460				
Mixed	1.01	1.38	13,993	Mixed	0.69	1.65	11,454	Mixed	0.31	2.19	6,719				
Total	20.04	1.33	265,882	Total	13.16	1.62	213,098	Total	6.15	2.05	126,065				
Inferred				Inferred				Inferred							
Carbonatite	17.09	1.07	182,866	Carbonatite	8.64	1.35	116,967	Carbonatite	1.90	1.85	35,045				
Fenite	17.47	1.06	184,819	Fenite	8.27	1.35	111,318	Fenite	1.73	1.88	32,477				
Mixed	1.90	1.56	29,614	Mixed	1.68	1.65	27,863	Mixed	1.43	1.74	24,890				
Total	36.47	1.09	397,299	Total	18.59	1.38	256,149	Total	5.06	1.83	92,412				

Table 1 – In-situ Mineral Resource estimates at different cut–off grades¹

¹ Mineral resources which are not mineral reserves do not have demonstrated economic viability

The estimated mineral resource has been traced in drill holes to a maximum depth of 350 m below the surface of Songwe Hill and is based on the two phases of diamond drilling completed by Mkango in 2011 and 2012 totalling approximately 6,850 m. The vast majority of the Indicated mineral resource blocks (at a 1% TREO cut-off, 9.1 mt of carbonatite, 0.67 mt of mixed and 1.04 mt of fenite) are at depths of less than 200 m below the surface of the hill. The areas drilled to date are in an elevated position on the northern slopes of Songwe Hill, which rises approximately 230 m above the surrounding plain. The approximate dimensions of the mineral resource estimate are 400 m aligned northeast by 230 m aligned northwest and to a depth of 350 m below and paralleling the topographic surface of the hill and surrounding plain.

Higher grade areas occur at various locations within the mineral resource, including at or close to surface, particularly in the north eastern part of the carbonatite domain. The mineralisation is not constrained by drilling at depth and laterally to both the northeast and southwest.

Geological domains, comprising either carbonatite or fenite dominant rock types, were used to guide the mineral resource estimate. Where the carbonatite and fenite lithologies were inseparable, a mixed domain was created.

The carbonatite dominant domain generally comprises a higher proportion of elevated TREO grade mineralisation than the fenite dominant domain. This results in a higher proportion of the mineralisation in this domain being reported above the 1% TREO cut off, albeit at a similar average grade to the other domains, as illustrated in Table 2.

The carbonatite domain is dominant at Songwe, comprising 84% of the Indicated and 46% of the Inferred mineral resources.

A schematic geological map illustrating the location of the drill holes will shortly be made available on the Company's website (<u>www.mkango.ca</u>).

The individual REO data and ratios as presented in Tables 2, 3, 4 and 5 were derived from lengthweighted averages of the drill hole data. Heavy rare earths, as defined here, comprise europium, gadolinium, terbium, dysprosium, holmium, erbium, thulium, ytterbium, lutetium and yttrium. These include the most highly priced of the more commonly traded rare earths, europium, terbium and dysprosium.

The overall weighted average proportion of heavy rare earths as a percentage of total rare earths for Indicated and Inferred resource estimates at 1.0% TREO cut-off grade is 7.1% and 7.4% respectively. The heavy rare earths vary with cut-off grade both in terms of absolute values and relative proportions. As TREO grade decreases, relative proportions of heavy rare earths increases (at 0.5% TREO cut-off grade, the HREO proportion is 7.7% and 8.2% for Indicated and Inferred categories, respectively) and the reverse is also true (at 1.5% TREO cut-off grade, the HREO proportion is 6.1% and 5.8% for Indicated and Inferred categories, respectively).

Apart from the proportion of heavy rare earths, a further measure of the potential value is the proportions of critical rare earths. The US Department of Energy has highlighted neodymium, dysprosium, europium, terbium and yttrium as being "critical" rare earths in terms of their importance to the clean energy economy and risk of supply disruption. Of these, dysprosium, europium, terbium and yttrium are heavy rare earths and are also reflected in the heavy rare earth ratio. Neodymium (Nd) is a light rare earth, principally used in the production of high strength permanent magnets.

The Songwe Hill mineral resource has an estimated weighted average grade of 2,665 ppm Nd_2O_3 and 2,240 ppm Nd_2O_3 in the Indicated and Inferred categories at 1.0% TREO cut-off grade, respectively. This equates to a weighted average proportion of Nd_2O_3 as a percentage of total rare earth oxides for Indicated and Inferred categories of 16.5% and 16.3%, respectively, as derived from Table 2.

Metallurgical Scoping Test Work

Metallurgical scoping work at Mintek in South Africa is ongoing, comprising flotation test work and leach tests. The current flotation test work is focused on a similar reagent regime to that used previously at the Mountain Pass mine and variations thereof. Further reagent regimes and conditions will continue to be tested. Rare earth mineralogy at Songwe is well understood, comprising predominantly synchysite and apatite.

								In-situ	Indicated	Mineral I	Resource	at 1% TRE	O Cut-Of	f								
Indicated	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
Carbonatite	11.10	3,951	7,208	775	2,676	387	14,997	95	223	27	127	21	48	6	36	5	590	1,178	16,175	1.62	351	12
Fenite	1.37	3,980	7,235	779	2,679	404	15,077	76	186	24	116	19	46	6	32	4	542	1,050	16,127	1.61	301	11
Mixed	0.69	4,520	7,678	774	2,473	335	15,780	63	148	17	79	13	29	4	22	3	362	739	16,519	1.65	335	12
								In-situ	Inferred	Mineral R	esource a	t 1% TRE	O Cut-Off									
Inferred	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
Carbonatite	8.64	3,275	5,974	642	2,218	321	12,430	90	211	25	120	19	46	6	34	5	559	1,115	13,545	1.35	324	11
Fenite	8.27	3,286	5,973	643	2,212	333	12,448	73	180	23	112	18	44	5	31	4	523	1,014	13,462	1.35	295	12
Mixed	1.68	4,559	7,746	781	2,495	338	15,918	53	125	14	66	11	25	3	19	3	304	622	16,541	1.65	248	11

Table 2 – In-situ Mineral Resource estimates at 1.0% TREO cut-off grade¹

HREO – heavy rare earth oxides

Table 3 – REO distribution for different rock types at 1.0% TREO cut-off grade¹

				m-situ	multateu	winici ai ite	-source - N	LO DISTIL		1.0/0 IIIL							
Indicated	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
Carbonatite	24.43	44.56	4.79	16.54	2.39	0.59	1.38	0.17	0.78	0.13	0.30	0.04	0.22	0.03	3.65	100	7.3
Fenite	24.68	44.86	4.83	16.61	2.50	0.47	1.15	0.15	0.72	0.12	0.28	0.04	0.20	0.03	3.36	100	6.5
Mixed	27.36	46.48	4.69	14.97	2.03	0.38	0.90	0.10	0.48	0.08	0.18	0.02	0.13	0.02	2.19	100	4.5
				In-situ	Inferred N	/lineral Re	source - RE	O Distrib	utions at :	L.0% TREC	OCut-Off						
Inferred	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
Carbonatite	24.18	44.11	4.74	16.37	2.37	0.67	1.56	0.19	0.89	0.14	0.34	0.04	0.25	0.03	4.12	100	8.2
Fenite	24.41	44.37	4.78	16.43	2.48	0.54	1.33	0.17	0.83	0.14	0.33	0.04	0.23	0.03	3.89	100	7.5
Mixed	27.56	46.83	4.72	15.08	2.04	0.32	0.75	0.09	0.40	0.06	0.15	0.02	0.11	0.02	1.84	100	3.8

In-situ Indicated Mineral Resource - REO Distributions at 1.0% TREO Cut-Off

¹ Mineral resources which are not mineral reserves do not have demonstrated economic viability

Key assumptions, parameters and methods used to estimate the Mineral Resources

- wireframing of the three lithological units was based on surface geological mapping extended to depth using the drillhole intersection data;
- TREO, HREO, Th and U grades as well as Density were determined using Ordinary Kriging interpolation into individual 3-Dimensional block models constrained by the respective lithological wireframes;
- the lithological block models comprised sub-celled block dimensions of 5 m x 5 m x 5 m.
- the lithology wireframes and block models were truncated to the topographic surface;
- no capping or cutting to limit any input grade data was undertaken as part of the mineral resource estimation;
- Datamine Studio 3 was the modelling package; and
- mineral resources were classified as either Indicated or Inferred following an assessment of the grade and geological continuity exhibited by the data.

Scientific and technical information, including data verification, contained in this release has been approved and verified by Dr. Scott Swinden of Swinden Geoscience Consultants Ltd, who is a "Qualified Person" in accordance with National Instrument 43-101 – *Standards of Disclosure for Mineral Projects*.

Sample preparation and analytical work for the drilling and channel sampling programmes were provided by Intertek-Genalysis Laboratories (Johannesburg, South Africa and Perth, Australia) employing ICP-MS techniques suitable for rare earth element (REE) analyses and following strict internal QAQC procedures inserting duplicates, blanks and standards. Internal Laboratory QAQC was also completed to include blanks, standards and duplicates.

The Songwe Hill Rare Earth Project

The Songwe Hill rare earth project is located within a 100% owned exclusive prospecting licence covering an area of 1,283 km² in southeast Malawi (the "Phalombe Licence"). Songwe is accessible by road from Zomba, the former capital, and Blantyre, the principal commercial town of Malawi. Total travel time from Zomba is approximately 2 hours, which will reduce as infrastructure continues to be upgraded in the area.

Mkango Resources Ltd.

Mkango's primary business is the exploration for rare earth elements and associated minerals in the Republic of Malawi. It holds, through its wholly owned subsidiary Lancaster, a 100% interest in two exclusive prospecting licenses covering a combined area of 1,751 km² in southern Malawi. The main exploration target is the Songwe Hill rare earth deposit, which features carbonatite hosted rare earth mineralisation and was subject to previous exploration in the late 1980s.

The Corporation's corporate strategy is to further delineate the rare earth mineralisation at Songwe Hill and secure additional rare earth element and other mineral opportunities in Malawi and elsewhere in Africa.

For further information, please contact:

Mkango Resources Ltd.	William Dawes	Alexander Lemon
Office +1 (403) 444 – 5979	Chief Executive Officer	President
Fax +1 (403) 351 – 1703	will@mkango.ca	<u>alex@mkango.ca</u>
www.mkango.ca		

Cautionary Note Regarding Forward-Looking Statements

This news release may contain forward-looking statements relating to the Corporation. Readers are cautioned not to place undue reliance on forward-looking statements, as there can be no assurance that the plans, intentions or expectations upon which they are based will occur. By their nature, forward-looking statements involve numerous assumptions, known and unknown risks and uncertainties, both general and specific, that contribute to the possibility that the predictions, forecasts, projections and other forward-looking statements will not occur, which may cause actual performance and results in future periods to differ materially from any estimates or projections of future performance or results expressed or implied by such forward-looking statements. Such factors and risks include, among others, the interpretation and actual results of current exploration activities; uncertainty of estimates of mineral resources, changes in project parameters as plans continue to be refined; future commodity prices; possible variations in grade or recovery rates; failure of equipment or processes to operate as anticipated; labour disputes and other risks of the mining industry; delays in obtaining governmental approvals or financing or in the completion of exploration.

The forward-looking statements contained in this press release are made as of the date of this press release. Except as required by law, the Corporation disclaims any intention and assume no obligation to update or revise any forward-looking statements, whether as a result of new information, future events or otherwise, except as required by applicable securities law. Additionally, the Corporation undertakes no obligation to comment on the expectations of, or statements made, by third parties in respect of the matters discussed above.

The TSX Venture Exchange has neither approved nor disapproved the contents of this press release.

Neither the TSX Venture Exchange nor its Regulation Services Provider (as that term is defined in the policies of the TSX Venture Exchange) accepts responsibility for the adequacy or accuracy of this release.

Appendix

Table 4 - In-situ Mineral Resource estimates at different cut-off grades

								In-	<i>situ</i> Indica	ated Carb	onatite N	lineral Res	ource									
Cut-Off	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
%TREO	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
0.5	16.31	3,274	5,973	642	2,217	321	12,426	85	200	24	114	18	44	6	32	4	530	1,058	13,484	1.35	322	12
1.0	11.10	3,951	7,208	775	2,676	387	14,997	95	223	27	127	21	48	6	36	5	590	1,178	16,175	1.62	351	12
1.5	5.26	5,022	9,163	985	3,401	492	19,063	103	241	29	137	22	52	7	39	5	639	1,275	20,338	2.03	385	12
								In-	situ Infer	red Carbo	natite Mi	neral Res	ource									
Cut-Off	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
%TREO	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
0.5	17.09	2,568	4,686	504	1,739	252	9,748	77	180	22	102	17	39	5	29	4	476	949	10,698	1.07	304	12
1.0	8.64	3,275	5,974	642	2,218	321	12,430	90	211	25	120	19	46	6	34	5	559	1,115	13,545	1.35	324	11
1.5	1.90	4,539	8,281	890	3,074	445	17,228	99	233	28	132	21	51	6	37	5	616	1,230	18,458	1.85	349	11
									<i>In-situ</i> Inc	licated M	ixed Mine	eral Resou	rce									
Cut-Off	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
%TREO	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
0.5	1.01	3,749	6,369	642	2,051	278	13,088	61	144	17	76	12	29	4	22	3	351	717	13,805	1.38	318	12
1.0	0.69	4,520	7,678	774	2,473	335	15,780	63	148	17	79	13	29	4	22	3	362	739	16,519	1.65	335	12
1.5	0.31	6,051	10,280	1,037	3,311	448	21,127	69	163	19	87	14	32	4	25	3	399	816	21,943	2.19	387	14
									<i>In-situ</i> In	ferred Mi	xed Mine	ral Resou	rce									
Cut-Off	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
%TREO	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
0.5	1.90	4,289	7,287	735	2,347	318	14,976	53	125	15	66	11	25	3	19	3	305	624	15,600	1.56	251	11
1.0	1.68	4,559	7,746	781	2,495	338	15,918	53	125	14	66	11	25	3	19	3	304	622	16,541	1.65	248	11
1.5	1.43	4,802	8,158	823	2,628	356	16,766	53	124	14	66	11	25	3	19	3	302	618	17,384	1.74	243	11
-									<i>In-situ</i> Inc	licated Fe	enite Mine	eral Resou	rce									
Cut-Off	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
%TREO	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
0.5	2.71	2,876	5,228	563	1,936	292	10,895	64	158	20	98	16	39	5	27	4	459	889	11,784	1.18	288	13
1.0	1.37	3,980	7,235	779	2,679	404	15,077	76	186	24	116	19	46	6	32	4	542	1,050	16,127	1.61	301	11
1.5	0.59	5,236	9,517	1,025	3,524	531	19,833	88	217	28	135	22	53	7	38	5	633	1,226	21,060	2.11	334	10
							-			ferred Fe	nite Mine	ral Resou	rce									
Cut-Off	Million	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	LREO	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	HREO	TREO	TREO	Th	U
%TREO	Tonnes	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	ppm	%	ppm	ppm
0.5	17.47	2,564	4,661	502	1,726	260	9,713	62	153	19	95	16	38	5	26	4	446	863	10,577	1.06	271	13
1.0	8.27	3,286	5,973	643	2,212	333	12,448	73	180	23	112	18	44	5	31	4	523	1,014	13,462	1.35	295	12
1.5	1.73	4,631	8,417	907	3,117	470	17,541	88	215	27	134	22	53	7	37	5	627	1,215	18,756	1.88	331	11

In-situ Indicated Carbonatite Mineral Resource

		In-	<i>situ</i> Indic	ated Carb	onatite M	ineral Res	ource - REC) Distribut	tions at 0.	5%, 1.0%	and 1.5%	TREO Cut	:-Offs				
Cut-Off	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
%TREO	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
0.5	24.28	44.29	4.76	16.44	2.38	0.63	1.49	0.18	0.84	0.14	0.32	0.04	0.24	0.03	3.93	100	7.8
1	24.43	44.56	4.79	16.54	2.39	0.59	1.38	0.17	0.78	0.13	0.30	0.04	0.22	0.03	3.65	100	7.3
1.5	24.69	45.05	4.84	16.72	2.42	0.51	1.19	0.14	0.67	0.11	0.26	0.03	0.19	0.03	3.14	100	6.3
		In	-situ Infei	rred Carbo	onatite Mi	neral Reso	urce - REO	Distributi	ions at 0.5	5%, 1.0% a	and1.5% 1	REO Cut-	Offs				
Cut-Off	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd_2O_3	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
%TREO	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
0.5	24.01	43.80	4.71	16.26	2.35	0.72	1.68	0.20	0.95	0.15	0.37	0.05	0.27	0.04	4.45	100	8.9
1	24.18	44.11	4.74	16.37	2.37	0.67	1.56	0.19	0.89	0.14	0.34	0.04	0.25	0.03	4.12	100	8.2
1.5	24.59	44.86	4.82	16.65	2.41	0.54	1.26	0.15	0.72	0.12	0.27	0.04	0.20	0.03	3.34	100	6.7
			In-situ In	dicated M	ixed Mine	ral Resour	ce - REO D	istribution	ns at 0.5%	, 1.0% an	d 1.5% TR	EO Cut-O	ffs				
Cut-Off	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd_2O_3	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
%TREO	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
0.5	27.15	46.13	4.65	14.86	2.01	0.44	1.04	0.12	0.55	0.09	0.21	0.03	0.16	0.02	2.54	100	5.2
1	27.36	46.48	4.69	14.97	2.03	0.38	0.90	0.10	0.48	0.08	0.18	0.02	0.13	0.02	2.19	100	4.5
1.5	27.58	46.85	4.72	15.09	2.04	0.32	0.74	0.09	0.40	0.06	0.15	0.02	0.11	0.02	1.82	100	3.7
	-		In-situ In	ferred Mi	xed Mine	ral Resourc	e - REO Di	stribution	s at 0.5%,	1.0% and	l 1.5% TR	EO Cut-Of	fs				
Cut-Off	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
%TREO	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
0.5	27.50	46.71	4.71	15.05	2.04	0.34	0.80	0.09	0.43	0.07	0.16	0.02	0.12	0.02	1.96	100	4.0
1	27.56	46.83	4.72	15.08	2.04	0.32	0.75	0.09	0.40	0.06	0.15	0.02	0.11	0.02	1.84	100	3.8
1.5	27.62	46.93	4.73	15.12	2.05	0.30	0.71	0.08	0.38	0.06	0.14	0.02	0.11	0.02	1.74	100	3.6
			In-situ Ind	dicated Fe	nite Mine	ral Resour	ce - REO Di	stributior	is at 0.5%	, 1.0% and	d 1.5% TR	EO Cut-Of	fs				
Cut-Off	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd_2O_3	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
%TREO	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
0.5	24.41	44.36	4.78	16.43	2.48	0.54	1.34	0.17	0.83	0.14	0.33	0.04	0.23	0.03	3.89	100	7.5
1	24.68	44.86	4.83	16.61	2.50	0.47	1.15	0.15	0.72	0.12	0.28	0.04	0.20	0.03	3.36	100	6.5
1.5	24.86	45.19	4.87	16.73	2.52	0.42	1.03	0.13	0.64	0.11	0.25	0.03	0.18	0.02	3.01	100	5.8
			In-situ In	ferred Fe	nite Mine	ral Resour	ce - REO Di	stribution	ns at 0.5%	, 1.0% and	d 1.5%TR	EO Cut-Of	fs				
Cut-Off	La ₂ O ₃	Ce ₂ O ₃	Pr ₂ O ₃	Nd ₂ O ₃	Sm ₂ O ₃	Eu ₂ O ₃	Gd ₂ O ₃	Tb ₂ O ₃	Dy ₂ O ₃	Ho ₂ O ₃	Er ₂ O ₃	Tm ₂ O ₃	Yb ₂ O ₃	Lu ₂ O ₃	Y ₂ O ₃	Total	HREO
%TREO	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%	%
0.5	24.25	44.07	4.75	16.32	2.46	0.59	1.45	0.18	0.90	0.15	0.36	0.04	0.25	0.03	4.21	100	8.2
1	24.41	44.37	4.78	16.43	2.48	0.54	1.33	0.17	0.83	0.14	0.33	0.04	0.23	0.03	3.89	100	7.5
1.5	24.69	44.88	4.83	16.62	2.50	0.47	1.15	0.15	0.71	0.12	0.28	0.04	0.20	0.03	3.34	100	6.5

Table 5 - REO distribution at different cut-off grades